

SKU	Tire Size	Load Range, [Ply]	Service Desc.	Side Wall	Rim Width		Max Load (Lbs.) at PSI		Overall Tire Diam. (in)	Section Width (in)	Tread Width (in)	Min. Dual Space w/o Chains	Rev Per Mile	Weight (lbs)	Tread Depth		Notes
					Meas.	Appr.	Dual	Single							32nds	mm	
L401	8.75R16.5LT	D	111/106N	BSW	(6.75)	6.0-6.7	2095 at 65	2405 at 65	29.50	8.60	6.08	9.90	705	34	14.0	11.1	DISC AST 8P 111/106N BW
L402	9.50R16.5LT	D	117/112N	BSW	(6.75)	6.7-8.2	2470 at 65	2835 at 65	30.30	9.20	6.70	10.70	684	38	14.0	11.1	DISC AST 8P 117/112N BW
L411	LT215/85R16	E	115/112Q	BSW	(6)	5.5-7.0	2470 at 80	2680 at 80	30.20	8.40	5.74	9.90	687	37	14.0	11.1	DISC AST 10P 115/112Q BW
L412	LT225/75R16	E	115/112Q	BSW	(6)	6.0-7.0	2470 at 80	2680 at 80	29.30	8.50	6.28	10.20	713	36	14.0	11.1	DISC AST LT Q BLK 115 Q BLK
L406	LT235/85R16	E	120/116N	BSW	(6.5)	6.0-7.0	2778 at 80	3042 at 80	31.50	9.30	6.11	10.80	658	40	14.0	11.1	DISC AST 10P 120/116N BW
L404	LT245/75R16	E	120/116N	BSW	(7)	6.5-8.0	2778 at 80	3042 at 80	30.40	9.40	6.61	11.30	682	39	14.0	11.1	DISC AST 10P 120/116N BW